

Beam Diagnostics and Instrumentation JUAS, Archamps Peter Forck Gesellschaft für Schwerionenforschnung (GSI)



Diagnostics is the 'organ of sense' for the beam. It deals with *real* beams in *real* technical installations including all imperfections. Three types of demands leads to different installations:

- Quick, non-destructive measurements leading to a single number or simple plots. Used as a check for online information. Reliable technologies have to be used.
 Example: Current measurement by transformers.
- Instrumentation for daily check, malfunction diagnosis and wanted parameter variation. *Example*: Profile measurement, in many cases 'intercepting' i.e destructive to the beam
- Complex instrumentation used for hard malfunction, commissioning and accelerator development.
 - The instrumentation might be destructive and complex.
 - *Example:* Emittance determination.
- A clear interpretation of the results is a important design criterion.
- Non-destructive ('non-intercepting') methods are preferred:
- ➤ The beam is not influenced
- \succ The instrument is not destroyed.

The Role of Beam Diagnostics

The cost of diagnostics is about 3 to 10 % of the total facility cost:

 ≥ 3 % for large accelerators *or* accelerators with standard technologies

 $\geq \approx 10$ % for versatile accelerators *or* novel accelerators and technologies.



The amount of man-power is about 10 to 20 %:

- ➤ very different physics and technologies are applied
- ➤ technologies have to be up-graded, e.g. data acquisition and analysis
- ➤ accelerator improvement calls for new diagnostic concepts.

Relevant physical Processes for Beam Diagnostics

Electro-magnetic influence by moving charges:

→ classical electro-dynamics, voltage and current meas., low and high frequencies *Examples:* Faraday cups, beam transformers, pick-ups

- **Emission of photon by accelerated charges: (only for electrons)**
 - \rightarrow optics, optical techniques (from visible to x-ray)
 - *Example:* Synchrotron radiation monitors
- >Interaction of particles with photons:
 - \rightarrow optics, lasers, optical techniques, particle detectors
 - Examples: laser scanners, short bunch length measurement, polarimeters
- >Coulomb interaction of charged particles with matter:
- \rightarrow atomic and solid state physics, current measurement, optics, particle detectors *Examples:* scintillators, viewing screens, ionization chambers, residual gas monitors
- >Nuclear- or elementary particle physics interactions:
 - \rightarrow nuclear physics, particle detectors
 - *Examples:* beam loss monitors, polarimeters, luminosity monitors
- >And of cause accelerator physics for proper instrumentation layout.

Beam diagnostics deals with the full spectrum of physics and technology,

 \Rightarrow this calls for experts on all these fields and is a challenging task!

Beam Quantities and their Diagnostics I

LINAC & transport lines: Single pass \leftrightarrow **Synchrotron**: multi pass **Electrons**: always relativistic \leftrightarrow **Protons/Ions**: non-relativistic for $E_{kin} < 1$ GeV/u **Depending on application**: Low current \leftrightarrow high current

Overview of the most commonly used systems:

Beam quantity		LINAC & transfer line	Synchrotron
Current I	General	Transformer, dc & ac	Transformer, dc & ac
		Faraday Cup	
	Special	Particle Detectors	Pick-up Signal (relative)
Profile x _{width}	General	Screens, SEM-Grids	Residual Gas Monitor
		Wire Scanners, OTR Screen	Wire Scanner,
			Synchrotron Light Monitor
	Special	MWPC, Fluorescence Light	
Position <i>x_{cm}</i>	General	Pick-up (BPM)	Pick-up (BPM)
	Special	Using position measurement	
Transverse Emittance ε_{tran}	General	Slit-grid	Residual Gas Monitor
		Quadrupole Variation	Wire Scanner
	Special	Pepper-Pot	Transverse Schottky

Beam Quantities and their Diagnostics II

Beam quantity		LINAC & transfer line	Synchrotron
Bunch Length Δφ	General	Pick-up	Pick-up
			Wall Current Monitor
	Special	Secondary electrons	Streak Camera, Laser
Momentum <i>p</i> and	General	Pick-ups (Time-of-Flight)	Pick-up (e.g. tomography)
Momentum Spread <i>Ap/p</i>	Special	Magnetic Spectrometer	Schottky Noise Spectrum
Longitudinal Emittance ε_{long}	General	Buncher variation	
	Special	Magnetic Spectrometer	Pick-up & tomography
Tune and Chromaticity Q, ξ	General		Exciter + Pick-up
	Special		Transverse Schottky Spectrum
Beam Loss r _{loss}	General	Particle Detectors	
Polarization <i>P</i>	General	Particle Detectors	
	Special	Laser Scattering (Compton scattering)	
Luminocity L	General	Particle Detectors	

>Destructive and non-destructive devices depending on the beam parameter.

 \succ Different techniques for the same quantity \leftrightarrow Same technique for the different quantities.

GSI

Example: Diagnostics Bench for the Commissioning of an RFQ



Demands for Beam Diagnostics

GSI

Typical Installation of a Diagnostics Device



Example: Graphical User Interface for Beam Position Monitors



The result helps to align the accelerator!

Some experimental device parameters are also shown to prove the functionality.

GSI

The Accelerator Facility at GSI



Outline of the Lecture

The ordering of the subjects is oriented by the beam quantities:

- Current measurement: Transformers, cups, particle detectors
- Profile measurement: Various methods depending on the beam properties
- Transverse emittance measurement: Destructive devices,

determination by linear transformations

- Pick-ups for bunched beams: Principle and realization of rf pick-ups, closed orbit and tune measurements
- Measurement of longitudinal parameters: Beam energy with pick-ups,

time structure of bunches for low and high beam energies, longitudinal emittance

Beam loss detection: Secondary particle detection for optimization and protection

It will be discussed: The action of the beam to the detector, the design of the devices, generated raw data, partly analog electronics, results of the measurements.
It will not be discussed: Detailed signal-to-noise calculations, analog electronics, digital electronics, data acquisition and analysis, online and offline software....
General: Standard methods and equipment for stable beams with moderate intensities.

Goal of the Lecture



The goal of the lecture should be:

- > Understanding the signal generation of various device
- > Showing examples for real beam behavior
- > Enabling a correct interpretation of various measurements.

FE 55 11